

Certificate of Analysis

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

1.0 ACCREDITATION / REGISTRATION

INORGANIC VENTURES is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



2.0 PRODUCT DESCRIPTION

Product Code: Multi Analyte Custom Grade Solution

Catalog Number: IV-STOCK-1643
Lot Number: T2-MEB720866
Matrix: 5% (v/v) HNO3

Value / Analyte(s): 32 000 µg/L ea: Calcium, 21 000 µg/L ea: Sodium, 8 000 µg/L ea: Magnesium, 2 000 $\mu g/L$ ea: Potassium, 544 µg/L ea: Barium, 323 µg/L ea: Strontium, 158 µg/L ea: Boron, 142 µg/L ea: Aluminum, 121 µg/L ea: Molybdenum, 113 µg/L ea: Rhenium, 98 μg/L ea: Iron, 79 µg/L ea: Zinc, 62 µg/L ea: Nickel, 60 µg/L ea: Arsenic, 58 μg/L ea: Antimony, 39 µg/L ea: Manganese, 38 µg/L ea: Vanadium, 27 μg/L ea: Cobalt, 23 µg/L ea: Copper, 20 µg/L ea: Chromium, Lead, 17 μg/L ea: Lithium, 14 µg/L ea: Beryllium, Bismuth, Rubidium,

12 μg/L ea: Selenium, 7 μg/L ea: Thallium,

Cadmium,

1 μg/L ea: Silver,

Tellurium

3.0 CERTIFIED VALUES AND UNCERTAINTIES

ANALYTE Aluminum, Al	CERTIFIED VALUE 142.1 ± 0.5 μg/L	ANALYTE Antimony, Sb	CERTIFIED VALUE 58.10 ± 0.44 µg/L
Arsenic, As	60.00 ± 0.43 μg/L	Barium, Ba	543.9 ± 3.0 μg/L
Beryllium, Be	14.00 ± 0.09 μg/L	Bismuth, Bi	14.00 ± 0.11 μg/L
Boron, B	158.0 ± 1.2 μg/L	Cadmium, Cd	7.00 ± 0.04 μg/L
Calcium, Ca	32 010.0 ± 170.0 μg/L	Chromium, Cr	20.00 ± 0.12 μg/L
Cobalt, Co	27.00 ± 0.15 μg/L	Copper, Cu	23.00 ± 0.13 μg/L
Iron, Fe	98.0 ± 0.5 μg/L	Lead, Pb	20.00 ± 0.11 μg/L
Lithium, Li	17.00 ± 0.09 μg/L	Magnesium, Mg	8 000.0 ± 40.0 μg/L
Manganese, Mn	39.00 ± 0.21 μg/L	Molybdenum, Mo	121.0 ± 0.7 μg/L
Nickel, Ni	62.00 ± 0.34 μg/L	Potassium, K	2 001 ± 10 μg/L
Rhenium, Re	113.0 ± 0.9 μg/L	Rubidium, Rb	14.00 ± 0.08 μg/L
Selenium, Se	12.00 ± 0.08 μg/L	Silver, Ag	1.000 ± 0.008 μg/L
Sodium, Na	21 010.0 ± 100.0 μg/L	Strontium, Sr	322.8 ± 1.6 μg/L
Tellurium, Te	1.000 ± 0.009 μg/L	Thallium, TI	7.00 ± 0.05 μg/L
Vanadium, V	38.00 ± 0.26 μg/L	Zinc, Zn	79.0 ± 0.4 μg/L

Density: 1.025 g/mL (measured at 20 \pm 4 °C)

Assay Information:

ANALYTE	METHOD	NIST SRM#	SRM LOT#
Ag	Calculated		See Sec. 4.2
Al	ICP Assay	3101a	140903
Al	EDTA	928	928
As	ICP Assay	3103a	100818
В	ICP Assay	3107	110830
Ва	ICP Assay	3104a	140909
Ва	Gravimetric		See Sec. 4.2
Ве	ICP Assay	3105a	090514
Ве	Calculated		See Sec. 4.2
Bi	ICP Assay	3106	180815
Bi	Calculated		See Sec. 4.2
Ca	ICP Assay	3109a	130213
Ca	EDTA	928	928
Cd	ICP Assay	3108	130116
Cd	EDTA	928	928
Cd	Calculated		See Sec. 4.2
Со	ICP Assay	3113	190630
Со	EDTA	928	928
Со	Calculated		See Sec. 4.2
Cr	ICP Assay	3112a	170630
Cr	Calculated		See Sec. 4.2
Cu	ICP Assay	3114	121207
Cu	EDTA	928	928
Cu	Calculated		See Sec. 4.2
Fe	ICP Assay	3126a	140812
Fe	EDTA	928	928
Fe	Calculated		See Sec. 4.2
K	ICP Assay	3141a	140813
K	Gravimetric		See Sec. 4.2
Li	ICP Assay	3129a	100714
Li 	Calculated		See Sec. 4.2
Li 	Gravimetric	0.404	See Sec. 4.2
Mg	ICP Assay	3131a	140110
Mg	EDTA	928	928
Mn	ICP Assay	3132	050429
Mn	EDTA	928	928
Mn	Calculated	2424	See Sec. 4.2
Mo	ICP Assay	3134	130418
Mo	Calculated	3152a	See Sec. 4.2
Na	ICP Assay	3152a	120715
Na	Gravimetric	2426	See Sec. 4.2
Ni Ni	ICP Assay EDTA	3136 928	120619 928
Ni Ni	Calculated	920	928 See Sec. 4.2
Pb	ICP Assay	3128	101026
Pb	EDTA	928	928
Pb	Calculated	020	926 See Sec. 4.2
Rb		3145a	150622
	IC Assay	J 17-Ja	
Rb	Gravimetric		See Sec. 4.2

Re	ICP Assay	3143	140825
Sb	ICP Assay	3102a	140911
Se	ICP Assay	3149	100901
Se	Calculated		See Sec. 4.2
Sr	EDTA	928	928
Sr	ICP Assay	Traceable to 3153a	K2-SR650985
Te	Calculated		See Sec. 4.2
TI	ICP Assay	3158	151215
TI	Calculated		See Sec. 4.2
V	ICP Assay	3165	160906
V	EDTA	928	928
Zn	ICP Assay	3168a	120629
Zn	EDTA	928	928
Zn	Calculated		See Sec. 4.2

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

Characterization of CRM/RM by Two or More Methods	Characterization of CRM/RM by One Method
Certified Value, X _{CRM/RM} , where two or more methods of characterization are used is the weighted mean of the results:	Certified Value, X _{CRM/RM} , where one method of characterization is used is the mean of individual results:
$X_{CRM/RM} = \Sigma(w_i) (X_i)$	$X_{CRM/RM} = (X_a) (u_{char} a)$
X _i = mean of Assay Method i with standard uncertainty u _{char i}	X _a = mean of Assay Method A with
$\mathbf{w_i}$ = the weighting factors for each method calculated using the inverse square of the variance:	uchar a = the standard uncertainty of characterization Method A
$\mathbf{w_i} = (1/u_{\text{char i}})^2 / (\Sigma(1/(u_{\text{char i}})^2)$	
CRM/RM Expanded Uncertainty (±) = $U_{CRM/RM}$ = $k (u_{char}^2 + u_{bb}^2 + u_{lts}^2 + u_{ts}^2)^{1/2}$	CRM/RM Expanded Uncertainty (±) = $U_{CRM/RM} = k (u_{char}^2 + u_{bb}^2 + u_{lts}^2 + u_{ts}^2)^{1/2}$
k = coverage factor = 2	k = coverage factor = 2
$u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{\frac{1}{2}}$ where u_{char} i are the errors from each characterization method	u _{char a} = the errors from characterization
u _{bb} = bottle to bottle homogeneity standard uncertainty	ubb = bottle to bottle homogeneity standard uncertainty
u _{lts} = long term stability standard uncertainty (storage)	u _{lts} = long term stability standard uncertainty (storage)
u _{ts} = transport stability standard uncertainty	uts = transport stability standard uncertainty

4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

5.0 TRACE METALLIC IMPURITIES (TMI) DETERMINED BY ICP-MS AND ICP-OES (μg/mL) N/A

INTENDED USE

6.0

- For the calibration of analytical instruments and validation of analytical methods as appropriate.

7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between 4° 24° C to minimize the effects of transpiration. Use at $20^{\circ} \pm 4^{\circ}$ C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.inorganicventures.com/TCT

Note: This solution contains Silver (Ag), please refer to our Sample Preparation Guide for more information.

https://www.inorganicventures.com/sample-preparation-guide/samples-containing-silver

8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

10.0 QUALITY STANDARD DOCUMENTATION

10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganic ventures.com; info@inorganic ventures.com

11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

11.1 Certification Issue Date

July 01, 2022

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

11.2 Lot Expiration Date

- July 01, 2027
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

11.3 Period of Validity

- Sealed TCT Bag Open Date:

- This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.

12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Approved By:

Thomas Kozikowski

Thomas Kozikowski Manager, Quality Control DD978hi.

Certifying Officer:

Paul Gaines Chairman / Senior Technical Director