

# Certificate of Analysis

300 Technology Drive Christiansburg, VA 24073 USA inorganicventures.com P: 800-669-6799/540-585-3030 F: 540-585-3012 info@inorganicventures.com

#### 1.0 ACCREDITATION / REGISTRATION

**INORGANIC VENTURES** is accredited to ISO 17034, "General Requirements for the Competence of Reference Material Producers" and ISO/IEC 17025, "General Requirements for the Competence of Testing and Calibration Laboratories". Inorganic Ventures is also an ISO 9001 registered manufacturer (QSR Certificate Number QSR-1034).



#### 2.0 PRODUCT DESCRIPTION

Product Code: Multi Analyte Ion Chromatography Solution

Catalog Number: IV-STOCK-61
Lot Number: U2-MEB735192

Matrix: H2O

Value / Analyte(s):

30 µg/mL ea:

o-Phosphate, Sulfate,

20 µg/mL ea:

Bromide, Chloride, Nitrate, Nitrite,

10 μg/mL ea: Fluoride

#### 3.0 CERTIFIED VALUES AND UNCERTAINTIES

**ANALYTE CERTIFIED VALUE CERTIFIED VALUE ANALYTE**  $20.00 \pm 0.10 \mu g/mL$  $20.00 \pm 0.09 \ \mu g/mL$ Bromide, Br Chloride, Cl 10.00 ± 0.03 μg/mL 20.00 ± 0.08 μg/mL Fluoride, F-Nitrate, NO3-20.00 ± 0.10 μg/mL  $30.00 \pm 0.10 \mu g/mL$ Nitrite, NO2o-Phosphate, PO4

Sulfate, SO4 30.00 ± 0.15 μg/mL

**Density:** 0.999 g/mL (measured at 20 ± 4 °C)

#### **Assay Information:**

ANALYTE	METHOD	NIST SRM#	SRM LOT#		
Br	IC Assay	3184	151130		
Br	Fajans	999c	999c		
CI	IC Assay	3182	060925		
CI	Fajans	999с	999c		
F-	IC Assay	3183	140203		
NO3-	IC Assay	3185	050517		
NO2-	Calculated	8040	8040		
NO2-	IC Assay		traceable to 40h		
PO4	IC Assay	3186	170606		
SO4	IC Assay	3181	080603		

- The Calculated Value is a value calculated from the weight of a starting material that has been certified directly vs. a National Institute of Standards and Technology (NIST) SRM/RM. See Sec 4.2 for balance traceability.

The following equations are used in the calculation of the certified value and the uncertainty. Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k = 2.

#### Characterization of CRM/RM by Two or More Methods Characterization of CRM/RM by One Method Certified Value, X<sub>CRM/RM</sub>, where one method of characterization is used is the mean of individual results: Certified Value, $X_{CRM/RM}$ , where two or more methods of characterization are used is the weighted mean of the results: $X_{CRM/RM} = \Sigma(w_i) (X_i)$ $X_{CRM/RM} = (X_a) (u_{char\ a})$ X<sub>i</sub> = mean of Assay Method i with standard uncertainty u<sub>char i</sub> X<sub>a</sub> = mean of Assay Method A with $\mathbf{u_{char}}_{a}$ = the standard uncertainty of characterization Method A w<sub>i</sub> = the weighting factors for each method calculated using the inverse square of the variance: $\mathbf{w_i} = (1/\mathsf{u_{char\ i}})^2 \, / \, (\Sigma (1/(\mathsf{u_{char\ i}})^2)$ CRM/RM Expanded Uncertainty (±) = U<sub>CRM/RM</sub> = k (u<sup>2</sup><sub>char</sub> + u<sup>2</sup><sub>bb</sub> + u<sup>2</sup><sub>lts</sub> + u<sup>2</sup><sub>ts</sub>)<sup>1/2</sup> CRM/RM Expanded Uncertainty (±) = $U_{CRM/RM} = k (u^2_{char} a + u^2_{bb} + u^2_{lts} + u^2_{ts})^{1/2}$ k = coverage factor = 2 $u_{char} = [\Sigma((w_i)^2 (u_{char})^2)]^{1/2}$ where $u_{char}$ are the errors from each characterization method $\mathbf{u}_{\mathbf{char}\;\mathbf{a}}$ = the errors from characterization $\mathbf{u_{bb}}$ = bottle to bottle homogeneity standard uncertainty ubb = bottle to bottle homogeneity standard uncertainty ults = long term stability standard uncertainty (storage) u<sub>lts</sub> = long term stability standard uncertainty (storage) uts = transport stability standard uncertainty $\mathbf{u_{ts}}$ = transport stability standard uncertainty

#### 4.0 TRACEABILITY TO NIST

- This product is traceable to NIST via an unbroken chain of comparisons. The uncertainties for each certified value are reported, taking into account the SRM/RM uncertainty error and the measurement, weighing and volume dilution errors. In rare cases where no NIST SRM/RM are available, the term 'in-house std.' is specified.

#### 4.1 Thermometer Calibration

- All thermometers are NIST traceable through thermometers that are calibrated by an accredited calibration laboratory.

#### 4.2 Balance Calibration

- All analytical balances are calibrated by an accredited calibration laboratory and procedure. The weights used for testing are annually compared to master weights and are traceable to NIST.

#### 4.3 Glassware Calibration

- An in-house procedure is used to calibrate all Class A glassware used in the manufacturing and quality control of CRM/RMs.

### 5.0 CHROMATOGRAM

N/A

#### 6.0 INTENDED USE

- **6.1** This standard is intended for the calibration of analytical instruments and validation of analytical methods as appropriate. This CRM may be used in connection with EPA Methods 6010, 6020 (all versions), Standard Methods 3120 B and USP <232> / ICH Q3D.
- **6.2** For products attaining traceability through Inorganic Ventures' Primary Certified Reference Materials (PCRM™) see the Limited License to Use PCRM™ in the Inorganic Ventures <u>Terms and Conditions of Sale</u>, <a href="https://www.inorganicventures.com/terms-and-conditions-sale">https://www.inorganicventures.com/terms-and-conditions-sale</a>. The Terms and Conditions contain information on the use of materials traceable to PCRM™ certified reference materials. This Limited License agreement is especially pertinent for laboratories accredited under ISO:17034.

#### 7.0 INSTRUCTIONS FOR THE CORRECT USE OF THIS REFERENCE MATERIAL

#### 7.1 Storage and Handling Recommendations

- Store between approximately 4° 30° C while in sealed TCT bag.
- While stored in the sealed TCT bag, transpiration of this CRM/RM is negligible. After opening the sealed TCT bag transpiration of the CRM/RM will occur, resulting in a gradual increase in the analyte concentration(s). It is the responsibility of the user to account for this effect. When the bottle is weighed both before and after being placed in storage, the mass difference observed will be a measure of transpiration mass loss.
- After opening the sealed TCT bag, keep cap tightly sealed when not in use and store between  $4^{\circ}$   $24^{\circ}$  C to minimize the effects of transpiration. Use at  $20^{\circ} \pm 4^{\circ}$  C to minimize volumetric dilution error when using the reported density. Do not pipette from the container. Do not return removed aliquots to container.
- For more information, visit www.inorganicventures.com/TCT

#### 8.0 HAZARDOUS INFORMATION

- Please refer to the Safety Data Sheet for information regarding this CRM/RM.

#### 9.0 HOMOGENEITY

- This solution was mixed according to an in-house procedure and is guaranteed to be homogeneous. Homogeneity data indicate that the end user should take a minimum sample size of 0.2 mL to assure homogeneity.

#### 10.0 QUALITY STANDARD DOCUMENTATION

#### 10.1 ISO 9001 Quality Management System Registration

- QSR Certificate Number QSR-1034

#### 10.2 ISO/IEC 17025 "General Requirements for the Competence of Testing and Calibration Laboratories"

- Chemical Testing - Accredited / A2LA Certificate Number 883.01

#### 10.3 ISO 17034 "General Requirements for the Competence of Reference Material Producers"

- Reference Material Producer - Accredited / A2LA Certificate Number 883.02

Inorganic Ventures, 300 Technology Drive, Christiansburg, Va. 24073, USA; Telephone: 800.669.6799; 540.585.3030, Fax: 540.585.3012; inorganicventures.com; info@inorganicventures.com

#### 11.0 CERTIFICATION, LOT EXPIRATION AND PERIOD OF VALIDITY

#### 11.1 Certification Issue Date

August 02, 2023

- The certification is valid within the measurement uncertainty specified provided the CRM/RM is stored and handled in accordance with instructions given in Sec 7.1. This certification is nullified if instructions in Sec 7.1 are not followed or if the CRM/RM is damaged, contaminated, or otherwise modified.

### 11.2 Lot Expiration Date

- August 02, 2028
- The date after which this CRM/RM should not be used.
- The lot expiration date reflects the period of time that the stability of a CRM/RM can be supported by long term stability studies conducted on properly stored and handled CRM/RMs. Lot expiration is limited primarily by transpiration (loss of water from the solution) and infrequently by chemical stability.

#### 11.3 Period of Validity

- Sealed TCT Bag	Open Date:	

## 12.0 NAMES AND SIGNATURES OF CERTIFYING OFFICERS Certificate Prepared By:

Uyen Truong

**Custom Processing Supervisor** 

Mya Trum

Certificate Approved By:

Jodie Wall

Stock VSM Coordinator

Just Wall Parel R. Lainea

**Certifying Officer:** 

Paul Gaines

Chairman / Senior Technical Director

Page 4 of 4

<sup>-</sup> This CRM/RM should not be used longer than one year (or six months in the case of a 30 mL bottle) from the date of opening the aluminized bag or after the date given in Sec. 11.2, whichever comes first. This is contingent upon the CRM/RM being stored and handled in accordance with the instructions given in Sec. 7.1.